



PolyXeta®2

Sensor for toxic gases in zone 1, sealed

Microprocessor based gas sensor with 4 – 20 mA / RS485 Modbus output signal, alarm and fault relays (all SIL2 certified) for monitoring the ambient air to detect oxygen and toxic gases and vapors by means of an electrochemical sensor element (el.ch.) or an infrared sensor element. The calibration of sensors without LCD display is carried out via the calibration device Cal PX or the PC software PC-Soft 80. Sensors with LCD display have an integrated calibration routine that is started from the outside by a permanent magnet without opening the housing. In case of an alarm or failure the backlight of sensors with LCD display changes from green to red. The gas sensor is sealed and thus the housing in zone 1 can be opened during operation at any time (Ex demb[ib]).



Sensor without display

APPLICATION

The PolyXeta®2 sensor is used in industrial areas like oil/gas industry, biogas plants, petrochemical industry, power plants etc. in Ex-Zone 1. The PolyXeta®2 sensor is also suitable for commercial areas like gas transfer stations etc. With the 4 – 20 mA / RS485-ModBus output signal the sensor is suitable for connection to the PolyGard®2 gas controller series by MSR-Electronic, as well as to any other controllers or automation devices. Optionally, the PolyXeta®2 sensor is also available with LCD display and relay output.

FEATURES

- ATEX and IEC Ex certificates MSR-Electronic for electrical Ex protection
- ATEX metrical test & SIL2 safety functions 4 – 20 mA, RS485 and relay
- Type "Ex demb[ib]" for opening in zone 1 without switching-off, pressure-resistant enclosure
- Continuous monitoring
- Microprocessor with 12 bit converter resolution
- Self-monitoring system
- Easy calibration, opening of the enclosure during operation possible (demb [ib])
- Calibration service by exchanging the sensor head
- Proportional 4 – 20 mA output
- Serial interface to the control center
- Reverse polarity protection
- Overload protection
- LCD display with status LEDs (optional)
- Alarm and fault signal relay (optional)



Sensor with LCD-display





PolyXeta®2

Sensor for toxic gases in zone 1, sealed

SPECIFICATIONS

ELECTRICAL

Power supply	16 – 28 V DC, 20 – 29 V AC
Power consumption (at 24 V DC)	90 mA, max. 130 mA
Control unit	Microprocessor with 12 bit converter resolution
Digital filter	Averaging in order to increase the EMC immunity
Visual indications	2 LEDs operation, alarm and communication
Analog output signal (active)	Proportional, overload and short-circuit proof, load $\leq 500 \Omega$ 4 – 20 mA = measuring range 3.0 < 4 mA = underrange > 20 – 21,2 mA = overrange 2 mA = fault > 21.8 mA = fault High
Serial interface	Serial data bus
Fault relay (optional)	Max. 30 V AC/DC, 1 A
Alarm relay (optional)	Max. 30 V AC/DC, 1 A
LCD (optional)	2 x 16 characters, 3 status LEDs, 4 menu operating elements

SENSOR DATA

Gas type	Toxic gases & oxygen	
Sensor element	Electrochemical	Infrared
Measuring range	See Ordering Information	0 – 100 % LEL
Response time	$t_{90} \leq$ depending on gas type	$t_{90} \leq 30$ sec.
Accuracy	Depending on gas type	± 1 % below 25% of measuring range
Repeatability	Depending on gas type	± 2 % of measuring range
Stabilization time	300 sec.	900 sec.
Warm-up time	Measuring mode after 120 sec.	Measuring mode after 60 sec.

ENVIRONMENTAL CONDITIONS

Humidity	20 to 90% RH (not condensing)
Operating temperature	-25 °C to +60 °C
Storage temperature	-5 °C to +30 °C
Pressure range	800 to 1200 mbar (80 to 120 kPa)
Air velocity	< 6 m/sec.

PHYSICAL CHARACTERISTICS

Case / colour	Die-cast aluminium / light grey RAL 7032
Dimensions (d x H)	95 x 82 mm
Weight	Ca. 1.3 kg
Protection class	Housing protection IP66 to IP68 (depending on the cable glands used) Gas inlet IP64, with option splash-proof IP65 (available end of 2016)
Mounting	Wall mounting (sensor head downwards)
Cable entry	1 x 3/8 in. (Ansi B1.20.1)
Wire connection	Spring-type terminal, 0.08 to 2.5 mm ² AWG 28 - 12
Wire length	Max. load 500 Ω (= wire resistance + controller input resistance)
ATEX / IEC Ex approval	CE 0158, II2G Ex d IIC T4 (pending)

CERTIFICATES

Electrical Ex protection:
Ex demb[ib] EN60079-0, -1, -11, -18 (zone 1)
Metrological approval: (pending)
EN 60079-29-1 for Ex gases
Functional safety (SIL2) (pending)
EN 50402
EN 61508-1, -2, -3
EN 50271

WARRANTY

1 year on material and workmanship (without the sensor)





PolyXeta®2

Sensor for toxic gases in zone 1, sealed

ORDERING INFORMATION

PX2 - 5 - X -XXXXX-X

OPTIONS

- Without option 0
- Relay-set (2) 1
- LCD display 2
- Relay set (2) + LCD display 3

		GAS TYPE		Sensor type	Measuring range
	0	E1110-H	Carbon monoxide CO	El. Chem.	0-500 ppm
	1	E1125-A	Ammonia NH ₃	El. Chem.	0-100 ppm
	2	E1125-B	Ammonia NH ₃	El. Chem.	0-200 ppm
	3	E1125-D	Ammonia NH ₃	El. Chem.	0-1000 ppm
		C1129-C	Nitrogen monoxide NO	El. Chem.	0-100 ppm
		E1130-B	Nitrogen dioxide NO ₂	El. Chem.	0-20 ppm
		E1189-C	Ethylene C ₂ H ₄	El. Chem.	0-200 ppm
		C1193-B	Chlorine Cl ₂	El. Chem.	0-5 ppm
		C1193-D	Chlorine Cl ₂	El. Chem.	0-20 ppm
		E1196-B	Sulphur dioxide SO ₂	El. Chem.	0-20 ppm
		E1197-A	Hydrogen sulphide H ₂ S	El. Chem.	0-50 ppm
		E1195-A	Oxygen O ₂	El. Chem.	0-25 vol %
		E1195-B	Oxygen O ₂	El. Chem.	0-21 vol %
		I1164-A	Carbon dioxide CO ₂	Infrared	0-5 vol %

ELECTRICAL CONNECTION

